

CPU Cooler

High performance thermal solutions

Choosing the wrong CPU cooler for a system can lead to serious overheating, resulting in system shutdowns and potential damage to CPUs. For industrial applications, the following CPU coolers fit the needs of various operating environments, where different levels of cooling are required.

Pentium® 4 (LGA-775)


130W

CF-775A-RS

High Performance Two Copper Pipes LGA 775 CPU Cooler, RoHS

	CF-775A-RS
Dimensions (D x W x H) (mm)	92x92x73
Material	Cu-Al
Bearing Type	Rifle
Capability (Watt)	130W
Fan speed (RPM)	3600
Noise level (dBA)	36.6~39.6
Life expectance (hrs)	40000
G.W. (g)	492

Heat Pipes Inside



Pentium® 4-M (LGA-775)


90W

CF-775B-RS

High Performance 1U LGA 775 CPU Cooler, w/ 7010 fan, Copper, RoHS

	CF-775B-RS
Dimensions (D x W x H) (mm)	90x90x25.1
Material	Cu
Bearing Type	Two ball
Fan speed (RPM)	4800
Noise level (dBA)	40.3~44.3
Life expectance (hrs)	50000
G.W. (g)	600

Pentium® 4 (LGA-775)


115W

CF-520-RS

High Performance LGA 775 socket CPU Cooler, RoHS

	CF-520-RS
Dimensions (D x W x H) (mm)	115x115x67
Material	Aluminum Alloy
Bearing Type	Two ball
Capability (Watt)	115W
Fan speed (RPM)	4500
Noise level (dBA)	47.5~51.5
Life expectance (hrs)	70000
G.W. (g)	635

Pentium® 4 (Socket-478)



115W

CF-478A-RS

High Performance Copper Socket 478 CPU Cooler, RoHS

	CF-478A-RS
Dimensions (D x W x H) (mm)	92x92x67
Material	Cu
Bearing Type	Rifle
Capability (Watt)	115W
Fan speed (RPM)	3600
Noise level (dBA)	39.6
Life expectance (hrs)	40000
G.W. (g)	390

Pentium® 4 (Socket 478)


86W

CF-478B-RS

High Performance Heat pipe Socket 478 1U CPU Cooler, RoHS

	CF-478BA-RS
Dimensions (D x W x H) (mm)	89x76x26
Material	Cu-Al
Bearing Type	Two ball
Capability (Watt)	86W
Fan speed (RPM)	4800
Noise level (dBA)	37
Life expectance (hrs)	40000
G.W. (g)	204

Pentium® 4 (Socket 478)


86W

CF-514-RS

High Performance Skiving Pentium 4 CPU Cooler, RoHS

	CF-514-RS
Dimensions (D x W x H) (mm)	83x70x55
Material	Aluminum Alloy
Bearing Type	Two ball
Capability (Watt)	86W
Fan speed (RPM)	4800
Noise level (dBA)	42.4
Life expectance (hrs)	50000
G.W. (g)	284

Pentium® 4


86W

CF-521-RS

High Performance Socket-478 Pentium 4 CPU Cooler, RoHS

	CF-521-RS
Dimensions (D x W x H) (mm)	60x60x47
Material	Al
Bearing Type	Two ball
Capability (Watt)	86W
Fan speed (RPM)	4800
Noise level (dBA)	37
Life expectance (hrs)	40000
G.W. (g)	173

Pentium® 4


76W

CF-522-RS

High Performance Socket-478 1U Pentium 4t CPU Cooler, RoHS

	CF-522-RS
Dimensions (D x W x H) (mm)	60x60x30
Material	Al
Bearing Type	Two ball
Capability (Watt)	76W
Fan speed (RPM)	4800
Noise level (dBA)	37
Life expectance (hrs)	50000
G.W. (g)	120