

CPU Cooler

High performance thermal solutions

Pentium® 3 (Socket 370/ 462/ 478)



CF-512-RS

High Performance Copper type Cooler support P4 CPU up to 2.5GHz, RoHS

	CF-512-RS
Dimensions (D x W x H) (mm)	60x60x29
Material	Cu
Bearing Type	Two ball
Capability (Watt)	30W
Fan speed (RPM)	4200
Noise level (dBA)	33
Life expectancy (hrs)	70000
G.W. (g)	260

Pentium® 3 (Socket 370/ 462/ 478)



CF-513-RS

High Performance Copper Base CPU Cooler support P4 CPU up to 3.06GHz, RoHS

	CF-513-RS
Dimensions (D x W x H) (mm)	80x62x68.7
Material	Aluminum Alloy
Bearing Type	Two ball
Fan speed (RPM)	6800
Noise level (dBA)	46
Life expectancy (hrs)	40000
G.W. (g)	320

Socket-486/ 586



CF-401

486 CPU Cooler, RoHS

	CF-401RS
Dimensions (D x W x H) (mm)	44.5x44x20
Material	Aluminum Alloy
Bearing Type	Two ball
Fan speed (RPM)	5000
Noise level (dBA)	23.2
Life expectancy (hrs)	70000
G.W. (g)	52

AMD (Socket AM2)

46W




CF-AM2-RS

Socket AM2 1U CPU Cooler, RoHS

	CF-AM2-RS
Dimensions (D x W x H) (mm)	83x69x30
Material	Cu-Al
Bearing Type	Two ball
Fan speed (RPM)	4800
Noise level (dBA)	38
G.W. (g)	220

Socket-7



CF-502-RS

Socket-7 CPU Cooler, RoHS

	CF-502-RS
Dimensions (D x W x H) (mm)	52x52x30
Material	Aluminum Alloy
Bearing Type	One ball one sleeve
Fan speed (RPM)	5000
Noise level (dBA)	30.5
Life expectancy (hrs)	30000
G.W. (g)	100

Bracket Cooling Fan



BF-02-RS

Bracket Cooling Fan, RoHS

	BF-02-RS
Dimensions (D x W x H) (mm)	112x90x21
Material	Plastic
Bearing Type	One ball
Fan speed (RPM)	2800
Noise level (dBA)	28
Life expectancy (hrs)	45000
G.W. (g)	107.5

Bracket Cooling Fan



BF-03-RS

Bracket Cooling Fan with 2 slots, RoHS

	BF-03-RS
Dimensions (D x W x H) (mm)	111 90.6 34.6
Material	Plastic
Bearing Type	One ball
Fan speed (RPM)	2800
Noise level (dBA)	31
Life expectancy (hrs)	35000
G.W. (g)	149

Socket-478, Retention Kit



CF-KIT02-RS

Socket 478 Retention kit full metal material, RoHS

- For Socket 478
- Dimension: 89x78x33(mm)
- Material: Steel
- Weight: 72g